




6063-T5 AA20Um Clear Aluminum Solar Panel Frame With Punch / Drill

Our Product Introduction

for more products please visit us on aluminumextrusion-profiles.com

Basic Information

- Place of Origin: China
- Brand Name: HT
- Certification: CA ,CE
- Minimum Order Quantity: 1 ton
- Packaging Details: Packed with EP ,Carton ,Pallet or wooden case
- Delivery Time: 20days
- Payment Terms: T/T ,L/C
- Supply Ability: 3000tons each month



Product Specification

- Product Name: Aluminum Solar Panel Frame
- Alloy: 6063,6061,6005
- Material: Aluminum
- Surface Treatment: Powder Spray Coated
- Deep Process: Milling, Drilling, Cutting
- Temper: T5
- Highlight: **aluminium solar panel frame, anodized aluminum frame**

Product Description

6063-T5 AA20Um Clear Aluminum Solar Panel Frame With Punch / Drill

Hentec has eight high-performance extrusion production lines and more than 100 sets of equipment for deep-processing of aluminum products that makes us realize production precision machining integration, such as CNC, punching machine, milling machine, drilling machine, cutting machine, etc. They make the mechanization and productivity have been further improved. At the same time, we also have different of surface processing equipments, such as anodizing, electrophoresis, powder coating and so on. In order to achieve to diversification development, our company put aluminum honeycomb and plate equipment into production to meet market.

Hentec passed the certificate of ISO9001 International Standard Quality Management System . At the same time, Hentec has instituted the enterprise tenet:"Quality first, Outstanding Management, Excellent Services and Constant Improvement." It guarantees the strategy of winning the market by producing high-quality products. In order to supply 100% high quality products, Hentec has equipped many multiple modern detection equipments. In the aspect of software, Hentec has made a set of standardized managerial system to try its best to realize scientific management, which enhances the overall profits.

Description:

Aluminum Extrusion Solar Panel Frame

Aluminum solar panel frame
 Material: 6063, 6061, T5/T6
 Mill finish, anodized, powder coated
 Cut, punch, drill
 ISO9001, SGS, RoHS
 Aluminum extrusion solar panel frame

Features:

Item	Solar Frame Aluminum Alloy Extrusion Profile with Customized Color
Material	Aluminium 6000 series alloy: such as 6063 6005 6061
Temper	T4 T5 T6
length	3-6 Meter per piece, or as your inquire
Shape	Round,square,flat,hollow,oval,triangle,U-profile,L-profile,T-profile,customized available
Thickness	General profile Thickness: 0.7 - 5.0mm
Deep process	CNC ,drilling ,milling ,cutting ,bending ,tapping ,welding ,assembling ,punching
Frame Section Size	30mm*35mm ,35mm*35mm ,35mm*40mm ,30mm*46mm ,35mm*45mm ,35mm*50mm etc



Specifications :

Item	Aluminum Extrusion Solar Panel Frame
Material	Alloy 6063, 6061 or according to customer' s choice
Temper	T3, T4, T5, T6
Surface	Anodize (clear, satin, bronze, black, golden, silver, other multicolor) , electrophoresis, powder coating, PVDF coating, wood grain painting, etc.
Color	Any color based on Standard Germany RAL Mark
MOQ	1 ton. Usually 12 tons for a 20 feet container; 24 tons for a 40 feet container.
Profile type	used as the frame of solar panel
Fabrication	1. Milling; 2. Drilling; 3. Bending; 4. Cutting.
Moulding	1. Using our moulds, free; 2. Using customer' s drawing, opening mould fee need to be paid.
Mould size	25*25, 35*35,30*46, 46*50, 30*25, 40*40 ,50*35,etc.We can provide customized aluminum solar frames upon to customers' request.
FOB Port	Shanghai, etc.

Our Advantages!













1. 22 years' experiences of manufacturing .
2. STRONG R&D: Help customers finalize the design, strong tool design ability,excellent pressing and surface treatment technology.
- 3.Strict quality management: ISO Administration system.
4. 24 hours on-line communication.Professional, Patient, Flexible.
5. High capacity of manufacturing and wide range of products.
6. Be able to provide secondary fabricating.
7. Small order is accepted.
8. Be able to provide one-stop supply solution.
9. Multiple payment methods: TT, LC, DP,OA.

太阳能系列 Solar energy series **HD太阳能系列型材图**

新图号 旧图号	简图	线密度 kg/m	新图号 旧图号	简图	线密度 kg/m
GT001 G701		0.987	GT007 G007		0.803
GT002 角码为GT001 G702		0.530	GT008 G008		0.633
GT003 G795		0.615	GT009 G009		0.494
GT004 G794		0.466	GT010 G010		0.496
GT005 G590		0.814	GT011 G011		0.388
GT006 G591		0.681	GT012 G012		0.290

209 线密度仅供参考，出货以实际磅重为准！













HD太阳能系列型材图 国家免检

新图号 旧图号	简图	线密度 kg/m	新图号 旧图号	简图	线密度 kg/m
GT013 G778		0.372	GT019 G599		0.665
GT014 G594		0.367	GT020 G846		0.400
GT015 G595		0.183	GT021 Z081		0.884
GT016 G596		0.248	GT022 Z082		1.228
GT017 G597		0.534	GT023 Z083		0.952
GT018 G598		0.339	GT024 Z084		1.073

线密度仅供参考，出货以实际称重为准！ 210

新图号	旧图号	简图	线密度 kg/m	新图号	旧图号	简图	线密度 kg/m
GT025			0.653	GT031			0.548
角码为GT026	G895			G893			
GT026			0.732	GT032			0.279
角码为GT026	G896			G894			
GT027			0.424	GT033			1.711
角码为GT026	G915			G913			
GT028			0.524	GT034			0.745
角码为GT026	G916			角码为GT033	G914		
GT029			1.300	GT035			0.398
角码为GT029	G822			G222			
GT030			0.567	GT036			0.754
角码为GT029	G823			角码为GT036	G224		

211 线密度仅供参考，出货以实际磅重为准！

新图号 旧图号	简图	线密度 kg/m	新图号 旧图号	简图	线密度 kg/m
GT037 G229		0.172	GT052		0.728
GT038 G230		0.374	GT054 角码为GT052		0.509
GT039 G889		0.626	GT055 角码为GT052		0.537
GT040 G888		0.756	GT061		0.161
GT041 角码为GT026 G187		0.692	GT062		0.340
GT042 角码为GT026 G789		0.443	GT063		0.209

新图号 旧图号	简图	线密度 kg/m	新图号 旧图号	简图	线密度 kg/m
GT064		0.394	GT076		0.698
GT068		0.497	GT077A		0.848
GT069		0.613	GT078A		0.635
GT070		0.312	GT079		0.524
GT071		0.687	GT080		0.651
GT072		0.378	GT081		0.395

213 线密度仅供参考，出货以实际磅重为准！

HD太阳能系列型材图 国家免检

新图号 旧图号	简图	线密度 kg/m	新图号 旧图号	简图	线密度 kg/m
GT082		0.245	GT088		0.677
GT083		0.267	GT089		0.558
GT084		0.519	GT091		0.580
GT085		0.646	G791		
GT086		0.674	GT092		0.967
GT087		0.655	G792		
			GT093		0.832
			GT094		1.519

线密度仅供参考，出货以实际磅重为准！ 214

Applications:

Competitive Advantage:

In addition to high quality ,we at Hentec office offer customer complete service .Our aluminum solar frame comes with a 15 year warranty .Maintenance service is also available .



 **HENTEC** Hentec Industry Co.,Ltd

 +86-13861643436  aluminum@hentec.com.cn  aluminumextrusion-profiles.com

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421