Our Product Introduction

6063 Alloy Alodine Aluminum Heatsink Extrusion Profiles With CNC **Machining**


Basic Information

. Place of Origin: China HENTEC . Brand Name: CA,CE · Certification: Minimum Order Quantity: 1 ton

Packaging Details: Ep paper ,kraft ,pallet

Delivery Time: 20days T/T ,L/C • Payment Terms:

• Supply Ability: 100 000ton each month



Product Specification

• Product Name: Aluminum Heatsink Extrusion Profiles

Alloy: 6063,6061,6005 • Material: Aluminum

Suface Treatment: Mill Finished, Anodized , Electrophoretic

Coated, Powder Spray Coated

• Deep Process: Milling, Drilling, Bending, Cutting

T4, T5, T6, T66 • Temper:

· Highlight: heatsink extrusion profiles,

aluminium extrusion heat sink profiles



Product Description

6063 Alloy Alodine Aluminum Heatsink Extrusion Profiles With CNC Machining

Advantage

- 1. We have our own factory and can provide products with good quality and competitive prices
- 2. Our products are exported to many countries and regions and have good reputation
- 3. Eco-friendly,safe,easy to use

Description:

- (1). Aluminum anodized profile for heat sink
- (2). 20 years warranty.
- (3). High corrosion resistance.
- (4). 5-10 years weather resistance.
- (5). Good wear resistance & anti-scratch.
- (6). Size customized.
- (7). Alloy temper:6061-T6,6063-T5,6082-T6,6005-T5,etc.
- (8). Standard: EN755, ASTMB221, DIN Standard
- (9). Surface treatment: Mill finishes; Anodized; Powder coated; Wooden grain, Electrophoresis, Machine/Acid polished and etc.
- (10). Applicant: industry, construction, exhibition, car, decoration and etc.
- (11). Packing details: Shrinking film, Carton, Wooden pallet or By customer's requirements.
- (12). Delivery: 25-30 days for mass production

Alloy:	6063	6061	6060	6005	6082					
Temper :	T5	Т6	T4							
Standard:	DIN	AAMA	AS	CHINAGB						
Certification:	ISO9001: 200	SO9001: 2008.								
Surface Finish:	Mill finish	Anodizing	Powder Coating	Wood Grain	Electrop horesis	Polishe d	Brushed			
Color:	Anodizing:	Silver, bronze, champagne, titanium, nickel, golden yellow, etc.								
		Anodizing thickness is up to 25um.								
	Powder Coating:	White, black, bronze, grey, green, etc.								
		Powder coating thickness is more than 60um.								
	Electrophores is:	Silver, nickel, golden yellow, black, champagne, etc								
	Polishing	Silver, nickel, golden yellow, black, etc								
	Brushing:	Silver, nickel, golden yellow, black, bronze, etc								
Machining:	Cutting, punching, drilling, bending, weld, mill, CNC, etc.									
OEM customized aluminium profiles are available.										

Applications:

Aluminum heat sink is widely used on Machines, cars, lighter...

Specifications:

1. Primary Technical Data

1)Chemical composition

Alloy	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Impurity	Al
6063	0.2-0.6	0.35	0.1	0.1	0.45-0.9	0.1	0.1	0.1	0.15	Rest
6061	0.4-0.8	0.7	0.15-0.4	0.15	0.8-1.2	0.04-0.35	0.25	0.15	0.15	Rest
6060	0.3-0.6	0.1-0.3	0.1	0.1	0.35-0.6	-	0.15	0.1	0.15	Rest
6005	0.6-0.9	0.35	0.1	0.1	0.40-0.6	0.1	0.1	0.1	0.15	Rest

2) Mechanical property

Alloy	Hemner	Tensile strength	Yield strength	Elongation	
6063	T5	≥ 160Mpa	≥ 110Mpa	≥ 8%	
0000	T6	≥ 205Mpa	≥ 180Mpa	≥ 8%	
6061	T6	≥ 265Mpa	≥ 245Mpa	≥ 8%	

Competitive Advantage:

- 1, This aluminum extraction profile for heat sink offers excellent engineering design and technical support .
- 2, With the deep processing ,it will be cut ,punched ,drilled ,milled and then fabricated into the finished product .
- 3, It is guaranteed on the excellent performance for as long as 15 years .



Tag: extruded aluminum heat sink aluminum heatsink extrusion profiles

♣HENTEC Hentec Industry Co.,Ltd



+86-13861643436



aluminum@hentec.com.cn



aluminumextrusion-profiles.com

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421