6063 / 6061 Slotted Aluminium Extrusion Assembly Line Connector / **Bracket**

Basic Information

. Place of Origin: China . Brand Name: Hentec

ISO14001:2004, ISO9001:2000 Certification:

Minimum Order Quantity:

 Packaging Details: Ep paper ,kraft ,pallet

Delivery Time: 20days T/T ,L/C • Payment Terms:

• Supply Ability: 100 000ton each month



Product Specification

• Product Name: Industrial Aluminium Profile

• Alloy: 6063 6061 • Material: Aluminum

Suface Treatment: Anodizing / Powder Painting • Deep Process: Milling, Drilling, Bending, Cutting

• Temper:

• Highlight: modular aluminium profile system,

aluminium extrusion frame system



Product Description

6063 / 6061 Aluminum Assembly Line / Connector / Aluminum T-Slot Bracket

- (1). Suitable for industry, architecture, transportation and so on.
- (2).20 years warranty.
- (3). High corrosion resistance.
- (4).5-10 years weather resistance.
- (5).Good wear resistance & anti-scratch.
- (6). Size customized.

Product Name	Industrial aluminium profile/ aluminum extrusion		
Profile Material	6063 aluminium alloy		
Temper	T5 T6		
Surface treatment	Mill finish, powder coating, anodizing, wooden grain coating, polishing, eletrophoresis, PVDF, sanding blasting, etc.		
The option of Profile	15/20/30/40/60/80/90/100 series etc.		
Slot width	6MM, 8MM, 10MM		
Color	Natural silver anodised, can be customised.		
Surface	Mill finish, Anodizeding, Sand Blasting, Powder coating, etc.		
Deep processing	Cutting, Drilling, Treading, Bending, etc.		
Application	Building & Construction, Industry, Machinery, Transportation, Electrical & Energy, Machinery, Radial profiles for LED cooling, Non-standard Automation, Structure Framing, etc		
Certification	ISO9001		
OEM & ODM	Acceptable		
Shipping Term	EXW, FOB, C&F or others can be discussed.		



Applications:

Mainly used for industrial production, such as automation equipment, enclosure of the skeleton and the companies according to their own customized mold machinery and equipment, such as assembly line conveyor, hoist, dispenser, testing equipment, shelves, etc., electronic machinery industries and clean room with a gain majority.



Specifications:

1.Primary Technical Data

1)Chemical composition

Alloy	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Impurity	Al
6063	0.2-0.6	0.35	0.1	0.1	0.45-0.9	0.1	0.1	0.1	0.15	Rest
6061	0.4-0.8	0.7	0.15-0.4	0.15	0.8-1.2	0.04-0.35	0.25	0.15	0.15	Rest
6060	0.3-0.6	0.1-0.3	0.1	0.1	0.35-0.6	-	0.15	0.1	0.15	Rest
6005	0.6-0.9	0.35	0.1	0.1	0.40-0.6	0.1	0.1	0.1	0.15	Rest

2)Mechanical property

Alloy	Temper	Tensile strength	Yield strength	Elongation
6063	T5	≥ 160Mpa	≥ 110Mpa	≥ 8%
	T6	≥ 205Mpa	≥ 180Mpa	≥ 8%
6061	T6	≥ 265Mpa	≥ 245Mpa	≥ 8%

公司图号	黄芪	载密度 kg/m
HT-745	40	1.292
HT-746	30	0.786
HT-747	50	2.524
HT-749	2000	0.464
HT-750	7.2 40 6.2	0.808
HT-751	60 8.2 10.4	1.616

公司图号	ЯH	线密度 kg/m
HT-752	40	1.646
HT-753	80 8.2 10.2	2.952
HT-754	45 2 0 5 1 0 0 5 1 0 0 8.2	2.015
HT-767	\$ 23.2 2.2 2.3	1.522

Competitive Advantage:

- 1)Engineering design and support.
 2)Aluminum profiles deeply processing:cutting,punching,drilling,milling,and fabricating.
 3)High Quality system, strictly inspection during production and whole inspection before package.
 4)Good performance, product warranty for 15 years.



⇒HENTEC Hentec Industry Co.,Ltd



+86-13861643436





Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421