Size Customized Aluminium Profile System Assembly Stage / Aluminum Extrusions

Basic Information

Place of Origin: ChinaBrand Name: Hentec

• Certification: ISO14001:2004, ISO9001:2000

Minimum Order Quantity: 1 ton

• Packaging Details: Ep paper ,kraft ,pallet

Delivery Time: 20daysPayment Terms: T/T ,L/C

• Supply Ability: 100 000ton each month



Product Specification

Product Name: Aluminum Profile System

Alloy: 6063Material: Aluminum

• Suface Treatment: Fluorocarbon Powder Spray Coated /PVDF

Paint, Drawbench, Steel Polished

• Deep Process: Milling, Drilling, Bending, Cutting

• Temper: T4, T5, T6

 Highlight: modular aluminium profile system, aluminium extrusion frame system HENTEC



Product Description

Size Customized Aluminium Profile System Assembly Stage / Aluminum Extrusion

Product Name	40x40mm Industrial aluminium profile/ aluminum extrusion
Profile Material	6063 aluminium alloy
Temper	T5
Surface	Mill finish, powder coating, anodizing, wooden grain coating, polishing,
treatment	eletrophoresis, PVDF, sanding blasting, etc.
The option of Profile	30/40/60/80/90/100 series etc.
Slot width	6MM,8MM,10MM
Color	Natural silver anodised, can be customised.
Surface	Mill finish, Anodizeding, Sand Blasting, Powder coating, etc.
Deep processing	Cutting, Drilling, Treading, Bending, etc.
Application	Building, Industry, Machinery
Certification	ISO9001
OEM & ODM	Acceptable



Applications:

Industry Aluminum profile used in cars, trains machinery ,electronics, medical and other industrial filed . In terms of hardware, machinery, electromechanical parts, solar PV products, aluminum frames are adopt as important auxiliary materials. We also have aluminum profiles for radiators, fitness machinery, buildings, lighting instrument, windpipes, oil pipelines, for instance.



Specifications:

1.Primary Technical Data

1)Chemical composition

Alloy	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Impurity	Al
6063	0.2-0.6			-	0.45-0.9	-	-	-		Rest
6061	0.4-0.8	0.7	0.15-0.4	0.15	0.8-1.2	0.04-0.35	0.25	0.15	0.15	Rest

6060	0.3-0.6	0.1-0.3	0.1	0.1	0.35-0.6	-	0.15	0.1	0.15	Rest
6005	0.6-0.9	0.35	0.1	0.1	0.40-0.6	0.1	0.1	0.1	0.15	Rest

2)Mechanical property

_,				
Alloy	Temper	Tensile	Yield strength	Flongation
Alloy	Temper	strength	Tield Strength	Liorigation
6063	T5	≥ 160Mpa	≥ 110Mpa	≥ 8%
0000	T6	≥ 205Mpa	≥ 180Mpa	≥ 8%
6061	T6	≥ 265Mpa	≥ 245Mpa	≥ 8%

公司图号	NH	线密度 kg/m
HT-745	10.2	1.292
HT-746	30	0.786
HT-747	50	2.524
HT-749	20 22 22 22 22 22 22 22 22 22 22 22 22 2	0.464
HT-750	7.2 40 6.2	0.808
HT-751	60 8.2 10.4	1.616

公司图号	# 16	线密度 kg/m
HT-752	40	1.646
HT-753	80 80 8.2 10.2	2.952
HT-754	45 2 0 5 1 0 0 5 1 0 0 1	2.015
HT-767	277	1.522

Competitive Advantage:

- 1)Engineering design and support.
 2)Aluminum profiles deeply processing:cutting,punching,drilling,milling,and fabricating.
 3)High Quality system, strictly inspection during production and whole inspection before package.
 4)Good performance, product warranty for 15 years.



⇒HENTEC Hentec Industry Co.,Ltd



+86-13861643436





Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421