T5 Cylinder Shell Industrial Aluminium Profile

Basic Information

. Place of Origin: China HENTEC . Brand Name: SGS · Certification: Minimum Order Quantity: 1 ton

Packaging Details: Ep paper ,kraft ,pallet

Delivery Time: 20days T/T ,L/C • Payment Terms:

• Supply Ability: 100 000ton each month

Product Specification

Product Name: Aluminum Cylinder

• Alloy: 6063,6061 Material: Aluminium

Suface Treatment: Anodized ,Electrophoretic Coated,Powder

Spray Coated

• Deep Process: Milling, Drilling, Cutting

T5, T6 • Temper:

· Highlight: aluminium profile t5,

aluminum 6061 extruded profiles



Product Description

Black Anodized Industrial Profile Systems / Aluminium Cylinder Shell

Item	OEM Aluminum Extrusion Profile
Materia I	6000 series Aluminium T4, T5, T6
Size / Thickn ess	General profiles thickness from 0.8 to 5.0mm, length from 3m-6m or customized available; Anodize protection film thickness from $8\sim25$ um, powder coating from $40\sim120$ um.
Shape	square, round, t shaped, rectangular, customized
Surfac e treatme nt	mill finish, anodizied , powder coating , wood grain, sand blasting , and so on
Colors	silver , black , blue, wood color , RAL powder coating color and so on
MOQ	500kgs for each item
FOB Port	Shanghai
payme nt terms	T/T 30% for deposit, balance before shipping.
settlem ent term	Charge by final actual weight or by drawing theoretical weight.

Applications:

Mainly used for industrial production, such as automation equipment, enclosure of the skeleton and the companies according to their own customized mold machinery and equipment, such as assembly line conveyor, hoist, dispenser, testing equipment, shelves, etc., electronic machinery industries and clean room with a gain majority.

Competitive Advantage:

- 1. Professional production workshop for extrusion and colored profile manufacturing,including we owr<u>#500 tons extrusion machine,automatic vertical electrophoresis production lines.</u>
- 2. Strict quality control and inspection before goods delivery.
- ${\it 3. Production standards: GB5237-2008 \ or \ other \ International \ standards.}$
- 4. With 15 years experience, our factory is well recognised by clients and enjoys a good reputation among overseas markets.
- 5. Professional R&D team .



FAQ For Saving Your Precious Time!

Q1: What's the thickness for anodizing?Can you do 15um? A: Our normal thickness is about 10 um.Yes, we can do 15um and above.

Q2: What color you can do for powder coating? The thickness for powder coat?

A: We can do any color for powder coat as long as you can provide the color sample. Our normally powder coating thickness is 60-80um.

Q3: What color you can do for wood grain?

A: Our most popular colors are Western Red Cedar, Australia Cedar, Jarrah I, Jarrah II, Chestnut, Bush Cherry, Bush Wood, Western Wood, Snow Gum, etc. If you need any other colors, we can do according to the color samples you provide.

Q4: How's the weather resistance for wood grain finish D1010?

A: (1).Powder:Akzo Noble Interpon D1010.

- (2). Wood grain film:Italian Menphis.
- (3). Standard complied: American AAMA Standard. 2603
- (4). UV test:1000 hours.
- (5). Salt spraying test:1000 hours.
- (6). Normal weather:10 years color guarantee.

Q5: What certification do you have? What's your standard?

A: We have ISO certification. Our standard is DIN, AAMA, AS/NZS, China GB.

Q6: What's the delivery time for samples and mass production?

A: (1).2-3 weeks to make the new moulds and make free samples.

(2). 3-4 weeks after receipt of deposit and confirmation of the order.

→ HENTEC Hentec Industry Co.,Ltd



+86-13861643436



aluminum@hentec.com.cn



aluminumextrusion-profiles.com

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421