Our Product Introduction



T4 V Slotted / T Slotted Custom Aluminium Extrusion For Industry

Basic Information

. Place of Origin: China

· Certification: CA ,CE ,ISO14001:2004, ISO9001:2000

• Minimum Order Quantity:

· Packaging Details: Ep paper ,kraft ,pallet

• Delivery Time: 20days Payment Terms: T/T ,L/C

. Supply Ability: 100 000ton each month



Product Specification

• Product Name: Industrial Aluminium Profile

• Alloy: 6063,6061,6005 • Material: Aluminum

Mill Finished, Anodized , Electrophoretic Suface Treatment:

Coated, Powder Spray

Coated, Drawbench, Steel Polished

Milling, Drilling, Bending, Cutting . Deep Process:

. Temper: T4, T5, T6

· Highlight: t4 slotted aluminum extrusion,

t slotted custom aluminium extrusion, t4 custom aluminium extrusion



More Images



Product Description

V-Slotted / T-Slotted Industrial Aluminum Profiles for Industry

We are aluminium profile and accessories manufacturer in WUXI, China. We offer competitive price!

we sincerely provide u with the most efficient, the most economical and the simplest composite service.

Description:

- 1. Alloy:6063,6061,6005 or according to customer's choice
- 2. Material:Aluminum
- 3. Suface Treatment: Mill Finished, Anodized , Electrophoretic coated, Powder spray coated, Fluorocarbon powder spray coated /PVDF Paint, Drawbench, Steel polished, Wood grain coated /Wooden transfer .
- 4. Deep process: Milling, Drilling, Bending, Cutting.



Applications:

Mainly used for industrial production, such as automation equipment, enclosure of the skeleton and the companies according to their own customized mold machinery and equipment, such as assembly line conveyor, hoist, dispenser, testing equipment, shelves, etc., electronic machinery industries and clean room with a gain majority.



Specifications:

1.Primary Technical Data

1)Chemical composition

Alloy	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Impurity	Al
6063	0.2-0.6	0.35	0.1	0.1	0.45-0.9	0.1	0.1	0.1	0.15	Rest
6061	0.4-0.8	0.7	0.15-0.4	0.15	0.8-1.2	0.04-0.35	0.25	0.15	0.15	Rest
6060	0.3-0.6	0.1-0.3	0.1	0.1	0.35-0.6	-	0.15	0.1	0.15	Rest
6005	0.6-0.9	0.35	0.1	0.1	0.40-0.6	0.1	0.1	0.1	0.15	Rest

2)Mechanical property

/						
Alloy	Temper	Tensile strength	Yield strength	Elongation		
6063	T5	≥ 160Mpa	≥ 110Mpa	≥ 8%		
0003	T6	≥ 205Mpa	≥ 180Mpa	≥ 8%		
6061	T6	≥ 265Mpa	≥ 245Mpa	≥ 8%		

公司图号	# 16	线密度 kg/m	公司图号	# 16	线密度 kg/m
HT-745	40	1.292	HT-752	40	1.646
HT-746	30	0.786	HT-753	80 80 8.2 10.2	2.952
HT-747	50	2.524	HT-754	45 2 0 7 1 0 0 1	2.015
HT-749	20	0.464	HT-767	5 7 10.2	1.522
HT-750	7.2 40 6.2	0.808			
HT-751	8.2 10.4	1.616			

Competitive Advantage:

- Engineering design and support.
 Aluminum profiles deeply processing:cutting,punching,drilling,milling,and fabricating.
 High Quality system, strictly inspection during production and whole inspection before package.
 Good performance, product warranty for 15 years.



⇒HENTEC Hentec Industry Co.,Ltd



+86-13861643436



aluminum@hentec.com.cn



aluminumextrusion-profiles.com

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421