



6063 / 6061 T5 T6 Aluminum Window Extrusion Profiles Wooden Transfer / Matted

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: HT
- Certification: CA ,CE
- Model Number: HD50
- Minimum Order Quantity: 1 ton
- Packaging Details: EP Paper ,kraft and pallet
- Delivery Time: 20days
- Payment Terms: T/T or L/C
- Supply Ability: 100 000 ton each month



Product Specification

- Material: Aluminum Alloy
- Temper: T5 / T6
- Alloy: 6063 / 6061 / 6060
- Surface: Anodized
- Color: Gold
- Highlight: **aluminum extrusion profiles,
extruded aluminium profiles**

Product Description

6063 / 6061 T5 T6 Aluminium Window Extrusion Profiles Wooden Transfer And Matted

Description:


1. Item **Sand Blasting And Anodizing Aluminum Window Profiles , Natural Color**
2. Material: aluminium alloy 6063/6061
3. Temper: T5 T6
4. Surface Treatment: anodizing, electrophoresis, powder coating, wooden transfer and matted.
5. Mould: 1) To do mould according to customers' request and drawing;
2) Produce 5 tons in a year at least, return the mould fee.
6. Aluminium ingot is A00 aluminium .
7. Length: about 4.2-6.8 meters.

Order, payment, terms, shipment

1. Minimum order: 500kg per trial order 1 piece of sample free of charge provided by approval and kept for future mass production.
2. Sample Lead Time: 25 working days (15 days for making the tool and 10 days making the samples. Before sending the samples to customer, samples should pass strict test in our lab.) Production Lead time: it depends on customers' order quantity (30 working days after deposit).
3. Payment: (Can negotiate with customers, our usual practices are as follow)
4. Tooling: 100% prepaid by T/T.
5. Parts: 30% upon order confirmation and balance before delivery by T/T

Applications:

Commercial center, hospital , school and airport , car , train , light , etc .



Specifications:

1. Primary Technical Data

1) Chemical composition

Alloy	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Impurity	Al
6063	0.2-0.6	0.35	0.1	0.1	0.45-0.9	0.1	0.1	0.1	0.15	Rest
6061	0.4-0.8	0.7	0.15-0.4	0.15	0.8-1.2	0.04-0.35	0.25	0.15	0.15	Rest
6060	0.3-0.6	0.1-0.3	0.1	0.1	0.35-0.6	-	0.15	0.1	0.15	Rest
6005	0.6-0.9	0.35	0.1	0.1	0.40-0.6	0.1	0.1	0.1	0.15	Rest

2) Mechanical property

Alloy	Temper	Tensile strength	Yield strength	Elongation
6063	T5	≥ 160Mpa	≥ 110Mpa	≥ 8%
	T6	≥ 205Mpa	≥ 180Mpa	≥ 8%
6061	T6	≥ 265Mpa	≥ 245Mpa	≥ 8%

Competitive Advantage:

1. Top Aluminium profile manufacturer for more than 10 years in China.
2. Diverse Products used in the fields of construction, industry and deep-processing.
3. Quality Control is put in the core position of our production.
4. Customized Production shows our capability in product design and process control.
5. Perfect Customer Services include careful packaging, quick delivery and good after-sale service.





Tag :

aluminium window extrusion profiles

powder coating aluminium window frames

 **HENTEC** Hentec Industry Co.,Ltd

 +86-13861643436

 aluminum@hentec.com.cn

 aluminumextrusion-profiles.com

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421