

Customerized Powder Spray Coated Frames For Solar Panels / 6063 / 6061 / 6060

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: HT
- Certification: CA ,CE
- Minimum Order Quantity: 1 ton
- Packaging Details: Packed with EP ,Carton ,Pallet or wooden case
- Delivery Time: 20days
- Payment Terms: T/T ,L/C
- Supply Ability: 3000tons each month



Product Specification

- Product Name: Aluminum Solar Panel Frame
- Alloy: 6063,6061,6005
- Material: Aluminum
- Surface Treatment: Mill Finished,Anodized ,Electrophoretic Coated,Powder Spray Coated
- Deep Process: Milling, Drilling, Bending,Cutting
- Temper: T4, T5, T6
- Highlight: **anodized aluminum frame,
solar panel aluminum frame**

Product Description

Customerized Aluminum Solar Panel Frame / 6063 6061 / 6060

Hentec has eight high-performance extrusion production lines and more than 100 sets of equipment for deep-processing of aluminum products that makes us realize production precision machining integration, such as CNC, punching machine, milling machine, drilling machine, cutting machine, etc. They make the mechanization and productivity have been further improved. At the same time, we also have different of surface processing equipments, such as anodizing, electrophoresis, powder coating and so on. In order to achieve to diversification development, our company put aluminum honeycomb and plate equipment into production to meet market.

Hentec passed the certificate of ISO9001 International Standard Quality Management System . At the same time, Hentec has instituted the enterprise tenet:"Quality first, Outstanding Management, Excellent Services and Constant Improvement." It guarantees the strategy of winning the market by producing high-quality products. In order to supply 100% high quality products, Hentec has equipped many multiple modern detection equipments. In the aspect of software, Hentec has made a set of standardized managerial system to try its best to realize scientific management, which enhances the overall profits.

Description:

Aluminum Extrusion Solar Panel Frame

Aluminum solar frame is widely used as the frame of solar panel, and then it is also called as aluminum solar panel frame. Our aluminum solar frames adopt L connector or screw joint, resulting in well fixed structure with durability. They are of high quality and at a competitive price.

Features:

- 1) 30*25 suitable for 30-120W solar modules
- 2) 35*35 suitable for 80-180W solar modules
- 3) 50*35 suitable for 160-220W solar modules
- 4) Many other custom made sizes available, such as: 45*35mm, 60*35mm, 46*40mm, 46*50mm, etc.




Specifications :

Alloy:	6063	6061	6060	6005	6082		
Temper :	T5	T6	T4				
Standard:	DIN	AAMA	AS	CHINAGB			
Certification:	ISO9001:2008.						
Surface Finish:	Mill finish	Anodizing	Powder Coating	Wood Grain	Electrophoresis	Polished	Brushed
Color:	Anodizing:	Silver, bronze, champagne, titanium, nickel, golden yellow, etc. Anodizing thickness is up to 25um.					
	Powder Coating:	White, black, bronze, grey, green, etc . Powder coating thickness is more than 60um.					
	Wood Grain:	1.Italian MENPHIS transfer printing paper. 2.AKZO NOBEL INTERPON D1010(10 years warranty):Australia cedar, Bush cherry, Chest nut, Jarrah I, Jarrah II, Western red cedar, etc. 3.AKZO NOBEL INTERPON D34(5 years warranty):Bush wood, Western red, Jarrah, Snow gum, etc.					
	Electrophoresis:	Silver, nickel, golden yellow, black, champagne, etc					
	Polishing	Silver, nickel, golden yellow, black, etc					













	Brushing:	Silver, nickel, golden yellow, black, bronze, etc
Machining:	Cutting, punching, drilling, bending, weld, mill, CNC, etc.	
OEM customized aluminium profiles are available.		

Our Advantages!

1. 22 years' experiences of manufacturing .
2. STRONG R&D: Help customers finalize the design, strong tool design ability,excellent pressing and surface treament technology.
- 3.Strict quality management: ISO Administration system.
4. 24 hours on-line communication.Professional, Patient, Flexible.
5. High capacity of manufaturing and wide range of products.
6. Be able to provide secondary fabricating.
7. Small order is accepted.
8. Be able to provide one-stop supply solution.
9. Multiple payment methods: TT, LC. DP,OA.



新图号	简 图	线密度 kg/m	新图号	简 图	线密度 kg/m
旧图号			旧图号		
GT001		0.987	GT007		0.803
G701			G007		
GT002		0.530	GT008		0.633
角码为GT001			G008		
G702					
GT003		0.615	GT009		0.494
G795			G009		
GT004		0.466	GT010		0.496
G794			G010		
GT005		0.814	GT011		0.388
G590			G011		
GT006		0.681	GT012		0.290
G591			G012		

新图号	简 图	线密度 kg/m	新图号	简 图	线密度 kg/m
旧图号			旧图号		
GT013		0.372	GT019		0.665
G778			G599		
GT014		0.367	GT020		0.400
G594			G846		
GT015		0.183	GT021		0.884
G595			Z081		
GT016		0.248	GT022		1.228
G596			Z082		
GT017		0.534	GT023		0.952
G597			Z083		
GT018		0.339	GT024		1.073
G598			Z084		

线密度仅供参考，出货以实际称重为准！ 210

新图号 旧图号	简 图	线密度 kg/m	新图号 旧图号	简 图	线密度 kg/m
GT025 角码为GT026		0.653	GT031		0.548
G895			G893		
GT026		0.732	GT032		0.279
G896			G894		
GT027 角码为GT026		0.424	GT033		1.711
G915			G913		
GT028 角码为GT026		0.524	GT034 角码为GT033		0.745
G916			G914		
GT029		1.300	GT035		0.398
G822			G222		
GT030 角码为GT029		0.567	GT036		0.754
G823			G224		

新图号 旧图号	简 图	线密度 kg/m	新图号 旧图号	简 图	线密度 kg/m
GT037 G229		0.172	GT052		0.728
GT038 G230		0.374	GT054 角码为GT052		0.509
GT039 G889		0.626	GT055 角码为GT052		0.537
GT040 G888		0.756	GT061		0.161
GT041 角码为GT026 G187		0.692	GT062		0.340
GT042 角码为GT026 G789		0.443	GT063		0.209

线密度仅供参考，出货以实际磅重为准！ 212

新图号	简图	线密度 kg/m
旧图号		
GT064		0.394
GT068		0.497
GT069		0.613
GT070		0.312
角码为 GT050		
GT071		0.687
GT072		0.378

新图号	简图	线密度 kg/m
旧图号		
GT076		0.698
角码为 GT050		
GT077A		0.848
GT078A		0.635
GT079		0.524
GT080		0.651
GT081		0.395

213 线密度仅供参考, 出货以实际磅重为准!

HD太阳能系列型材图 国家免检

新图号	简图	线密度 kg/m
旧图号		
GT082		0.245
GT083		0.267
GT084		0.519
GT085		0.646
GT086		0.674
GT087		0.655
GT088		0.677
GT089		0.558
GT091		0.580
GT092		0.967
GT093		0.832
GT094		1.519

线密度仅供参考，出货以实际磅重为准！ **214**

Applications:

Competitive Advantage:

In addition to high quality ,we at Hentec office offer customer complete service .Our aluminum solar frame comes with a 15 year warranty .Maintenance service is also available .



HENTEC Hentec Industry Co.,Ltd

+86-13861643436 aluminum@hentec.com.cn aluminumextrusion-profiles.com

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421