



Extruded Oxidize Aluminum Solar Panel Frame For Photovaltic Module

Basic Information

- Place of Origin: China
- Brand Name: Hentec
- Certification: CA ,CE
- Model Number: HT858
- Minimum Order Quantity: 1 ton
- Packaging Details: Packed with EP ,Carton ,Pallet or wooden case
- Delivery Time: 25days
- Payment Terms: T/T ,L/C
- Supply Ability: 3000tons each month



Product Specification

- Material: Aluminum Alloy
- Temper: T5
- Color: Silvery
- Application: Roof
- Size: 40*40mm
- Surface: Anodized
- Highlight: **aluminium solar panel frame,
solar panel aluminum frame**

Product Description

Extruded Oxidize Aluminum Solar Panel Frame For Photovoltaic Module

Our company Hentec has more than 15 years experience in manufacturing Aluminum and steel components and works strictly under ISO 9001 manufacturing standards . Hentec has a team of engineers ready to not only assist our customer but also their customers with any solar mounting solution design whether it be a small roof or large scale utility solar farm. We have years of experience in layout design, dealing with different soil and wind conditions, and rooftop design . Understanding that the most important part of solar pv solar installations is 'time', all of our products are carefully designed with fast installation always in mind.













Description :

Type:	Ground solar mounting
Installation site:	Open field ground
Material:	Aluminum6063 T3-T5;Steel
Fasten material:	Aluminum
Anticorrosive:	Hot-dip galvanized
Survival Wind Speed:	< 60m/s
Design Snow load:	Up to 1.4KN/ Square meters
Solar panel type:	Framed or Frameless
Panel Orientation:	Transverse or vertical
Design Standard:	CE;IOS9001
Quality warranty:	12-25 years
Duration:	More than 20 years
Delivery time:	7-15 days
Package:	Standard Packing

Specifications :













Item	Aluminum Extrusion Solar Panel Frame
Material	Alloy 6063, 6061 or according to customer' s choice
Temper	T3, T4, T5, T6
Surface	Anodize (clear, satin, bronze, black, golden, silver, other multicolor) , electrophoresis, powder coating, PVDF coating, wood grain painting, etc.
Color	Any color based on Standard Germany RAL Mark
MOQ	1 ton. Usually 12 tons for a 20 feet container; 24 tons for a 40 feet container.
Profile type	used as the frame of solar panel
Fabrication	1. Milling; 2. Drilling; 3. Bending; 4. Cutting.
Moulding	1. Using our moulds, free; 2. Using customer' s drawing, opening mould fee need to be paid.
Mould size	25*25, 35*35,30*46, 46*50, 30*25, 40*40 ,50*35,etc.We can provide customized aluminum solar frames upon to customers' request.
FOB Port	Shanghai, etc.

- 1.Alloy :6063,6061,6005 or according to customer' s choice
- 2.Material:Aluminum
- 3.Surface Treatment: Mill Finished,Anodized ,Electrophoretic coated,Powder spray coated,Fluorocarbon powder spray coated /PVDF Paint, Drawbench,Steel polished,Wood grain coated /Wooden transfer .
- 4.Deep process: Milling, Drilling, Bending,Cutting.
- 5.Application: Aluminum solar frame is widely used as the frame of solar panel.
- 6.Color:clear, satin, bronze, black, golden, silver, other multicolor
- 7.Temper: T4, T5, T6 ,T66

新图号	旧图号	简图	线密度 kg/m	新图号	旧图号	简图	线密度 kg/m
GT001	G701		0.987	GT007	G007		0.803
GT002	角码为GT001 G702		0.530	GT008	G008		0.633
GT003	G795		0.615	GT009	G009		0.494
GT004	G794		0.466	GT010	G010		0.496
GT005	G590		0.814	GT011	G011		0.388
GT006	G591		0.681	GT012	G012		0.290

209 线密度仅供参考，出货以实际磅重为准！

HD太阳能系列型材图 国家免检













新图号 旧图号	简图	线密度 kg/m	新图号 旧图号	简图	线密度 kg/m
GT013 G778		0.372	GT019 G599		0.665
GT014 G594		0.367	GT020 G846		0.400
GT015 G595		0.183	GT021 Z081		0.884
GT016 G596		0.248	GT022 Z082		1.228
GT017 G597		0.534	GT023 Z083		0.952
GT018 G598		0.339	GT024 Z084		1.073

线密度仅供参考，出货以实际称重为准！ 210

新图号	旧图号	简图	线密度 kg/m	新图号	旧图号	简图	线密度 kg/m
GT025			0.653	GT031			0.548
角码为GT026	G895			GT032	G893		
GT026			0.732	GT033			0.279
角码为GT026	G896			GT034	G894		
GT027			0.424	GT035			1.711
角码为GT026	G915			GT036	G913		
GT028			0.524	GT036			0.745
角码为GT026	G916			角码为GT033	G914		
GT029			1.300	GT036			0.398
角码为GT029	G822			角码为GT033	G222		
GT030			0.567	GT036			0.754
角码为GT029	G823			角码为GT033	G224		

211 线密度仅供参考，出货以实际磅重为准！

HD太阳能系列型材图 国家免检

新图号 旧图号	简图	线密度 kg/m	新图号 旧图号	简图	线密度 kg/m
GT037 G229		0.172	GT052		0.728
GT038 G230		0.374	GT054 角码为GT052		0.509
GT039 G889		0.626	GT055 角码为GT052		0.537
GT040 G888		0.756	GT061		0.161
GT041 角码为GT026 G187		0.692	GT062		0.340
GT042 角码为GT026 G789		0.443	GT063		0.209

线密度仅供参考，出货以实际磅重为准！ 212

新图号 旧图号	简图	线密度 kg/m	新图号 旧图号	简图	线密度 kg/m
GT064		0.394	GT076		0.698
GT068		0.497	GT077A		0.848
GT069		0.613	GT078A		0.635
GT070		0.312	GT079		0.524
GT071		0.687	GT080		0.651
GT072		0.378	GT081		0.395

213 线密度仅供参考，出货以实际磅重为准！

HD太阳能系列型材图 国家免检

新图号 旧图号	简图	线密度 kg/m	新图号 旧图号	简图	线密度 kg/m
GT082		0.245	GT088		0.677
GT083		0.267	GT089		0.558
GT084		0.519	GT091		0.580
GT085		0.646	G791		
GT086		0.674	GT092		0.967
GT087		0.655	G792		
			GT093		0.832
			GT094		1.519

线密度仅供参考，出货以实际磅重为准！ 214


Applications:

Competitive Advantage:

In addition to high quality ,we at Hentec office offer customer complete service .Our aluminum solar frame comes with a 15 year warranty .Maintenance service is also available .

 **HENTEC** Hentec Industry Co.,Ltd

 +86-13861643436

 aluminum@hentec.com.cn

 aluminumextrusion-profiles.com

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421