Hentec Industry Co., Ltd aluminumextrusion-profiles.com

Powder Painted Aluminium Window Frames For Deep - Processing Aluminum CE

Basic Information

Place of Origin: China
Brand Name: HT
Certification: CA ,CE
Minimum Order Quantity: 1 ton

Packaging Details: EP Paper ,kraft and pallet

Delivery Time: 20daysPayment Terms: T/T or L/C

• Supply Ability: 100 000 ton each month



Product Specification

Material: Aluminum Alloy

• Temper: T5 / T6

Alloy: 6063 / 6061 / 6060
Surface: Powder Painted
Color: Customerized

• Highlight: aluminum extrusion profiles,

profile aluminum extrusions

Product Description

Descrition:

Powder Painted Aluminium Door Profiles For Deep - Processing , Aluminum Window

Material: 6063

Surface: Mill Finished, Powder Coating, Chemical and Mechanical Polishing, Sand Blasting, Satin, Bronze, Black, Golden,

Silver, Anodizing, Electrophoresis

MOQ:10 sets

Packing: EPE, wrapped with waterproof paper, pallet, wooden case.

Sample delivery time: Two weeks

Order,payment,terms,shipment

1, Minimum order: 500kg per trial order 1 piece of sample free of charge provided by approval and kept for future mass production.

2, Sample Lead Time: 25 working days(15 days for making the tool and 10 days making the samples. Before sending the samples to customer, samples should pass strict test in our lab.)Production Lead time: it depends on customers' order quantity (30 working days after deposit).

3, Payment: (Can negotiate with customers, our usual practices are as follow)

4, Tooling:100% prepaid by T/T.

5, Parts:30% upon order confirmation and balance before delivery by T/T

Applications:

Aluminum profile used for making aluminum door .There are many colors can be selected for surface treatment .The strength can be increased by higher wall thickness . It is possible to produce according to customized design .



Specifications:

1. Primary Technical Data

1) Chemical composition

T) Chamical Composition										
Alloy	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Impurity	AI
6063	0.2-0.6	0.35	0.1	0.1	0.45-0.9	0.1	0.1	0.1	0.15	Rest
	0.4-0.8	-		0.15	0.8-1.2	0.04-0.35	0.25	0.15	0.15	Rest
	0.3-0.6		0.1	0.1	0.35-0.6	-	0.15	0.1	0.15	Rest
6005	0.6-0.9	0.35	0.1	0.1	0.40-0.6	0.1	0.1	0.1	0.15	Rest

2) Mechanical property

Alloy	Temper	Tensile strength	Yield strength	Elongation
6063	T5	≥ 160Mpa	≥ 110Mpa	≥ 8%
0003	T6	≥ 205Mpa	≥ 180Mpa	≥ 8%
6061	T6	≥ 265Mpa	≥ 245Mpa	≥ 8%

Competitive Advantage:

- 1. Top Aluminium profile manufacturer for more than 10 years in China.
- 2. Diverse Products used in the fields of construction, industry and deep-processing.
- 3. Quality Control is put in the core position of our production.
- Customized Production shows our capability in product design and process control.
 Perfect Customer Services include careful packaging, quick delivery and good after-sale service.



aluminium window extrusion profiles powder coating aluminium window frames



