6063 - T5 Aluminium Profile System Electrophoretic Coated for Bending **Cutting**

Basic Information

. Place of Origin: China · Certification: SGS • Minimum Order Quantity: 1 ton

· Packaging Details: Ep paper ,kraft ,pallet

• Delivery Time: 20days Payment Terms: T/T ,L/C

• Supply Ability: 100 000ton each month



Product Specification

• Product Name: Industrial Aluminium Profile

• Alloy: 6061,6005 • Material: Aluminum

Suface Treatment: Electrophoretic Coated, Powder Spray

Coated

• Deep Process: Bending, Cutting

T6,T66 • Temper:

· Highlight: modular aluminium profile system,

aluminium extrusion frame system



Product Description

Descrition:6063-T5 Industrial Aluminum Profiles , Aluminum Assembly Line

- 1) aluminum alloy:AL6063/6061/6005 or as for per customers's require.
- 2) finish. various anodizing colors, powder coating, paiting or mill finish.
- 3) Surface treatmen: andozied, electrophoresis, powder coating (any color), mill finish, color painting, and so on
- 4) Length: according to clients' need
- 5) Packing: with plastic film and wrapped with kraft paper.or meet the clients' requires
- 6) Usage of the aluminum products: decoration, furniture, windows and door frame, curtain wall, conatruction, etc. We have the Extruding machine (4500T).
- 7) Certificate: ISO9001.ISO14001

Order,payment,terms,shipment

- 1, Minimum order: 500kg per trial order 1 piece of sample free of charge provided by approval and kept for future mass production.
- 2, Sample Lead Time: 25 working days(15 days for making the tool and 10 days making the samples. Before sending the samples to customer, samples should pass strict test in our lab.)Production Lead time: it depends on customers' order quantity (30 working days after deposit).
- 3, Payment: (Can negotiate with customers, our usual practices are as follow)
- 4, Tooling:100% prepaid by T/T.
- 5, Parts:30% upon order confirmation and balance before delivery by T/T

Drawing no	Drawing	SMM kg/m
HT-745	40.2	1.292
HT-746	30	0.786
HT-747	50	2.524
HT-749	20	0.464
HT-750	7.2 6.2	0.808
HT-751	8.2 10.4	1.616

Drawing no	Drawing	SMM kg/m
HT-752	40	1.646
HT-753	80 8.2 10.2	2.952
HT-754	45 2 0 4 2 0 4 8.2	2.015
HT-767	45	1.522

Applications:

Mainly used for industrial production, such as automation equipment, enclosure of the skeleton and the companies according to their own customized mold machinery and equipment, such as assembly line conveyor, hoist, dispenser, testing equipment, shelves, etc., electronic machinery industries and clean room with a gain majority.

Competitive Advantage:

- 1.12 years' experiences of manufacturing, 10 years' exporting experiences .
- $2. \ STRONG \ R\&D: Help \ customers \ finalize \ the \ design, \ strong \ tool \ design \ ability, excellent \ pressing \ and \ surface \ treament \ technology.$
- 3. Strict quality management: ISO Administration system.
- 4. 24 hours on-line communication. Professional, Patient, Flexible.
- 5. High capacity of manufaturing and wide range of products.
- 6. Be able to provide secondary fabricating.
- 7. Small order isaccepted.
- 8. Be able to provide one-stop supply solution.



⇒HENTEC Hentec Industry Co.,Ltd



+86-13861643436



aluminum@hentec.com.cn



@ aluminumextrusion-profiles.com

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421