



OEM Aluminum Extrusions For Electronics / Electronic Enclosure with CNC Machining

Our Product Introduction

for more products please visit us on aluminumextrusion-profiles.com

Basic Information

- Place of Origin: China
- Brand Name: HT
- Certification: CA ,CE
- Minimum Order Quantity: 500pcs
- Packaging Details: Ep paper ,kraft ,pallet
- Delivery Time: 20days
- Payment Terms: T/T ,L/C
- Supply Ability: 100 000ton each month



Product Specification

- Product Name: Aluminum Heatsink Extrusion Profiles
- Alloy: 6063,6061,6005
- Material: Aluminum
- Surface Treatment: Mill Finished, Anodized ,Electrophoretic Coated, Powder Spray Coated
- Deep Process: Milling, Drilling, Bending, Cutting
- Temper: T4, T5, T6 ,T66
- Highlight: **extruded aluminium profiles, aluminium extrusion profiles**



Product Description

OEM Aluminum Extrusions For Electronics / Electronic Enclosure with CNC Machining

- 1) Quality material: 6063 (6061, 6060, 6005, 6082 available)
- 2) Machining: Lathe/mil/CNC/Polish/punch/drill/tap available
- 3) Finishing: Bright clear anodizing (powder coating/painting/silkscreening etc available)
- 4) Assembling and packaging
- 5) Application: For electronic
- 6) OEM design/specification is welcome.

Packing Method

- 1, Standard packing: Plastic sheet wrapped for each profile in order to protect the profiles' surfaces, kraft paper wrapped in bundles.
 - 2, Special packing: Wooden cases+iron trays.
 - 3, Bundles or boxes with wooden bars
 4. EPE+carton boxes.
 - 5, Customized packing methods are welcomed.
- Loading Weight
20'GP for 13tons, 40'GP for 20tons. LCL shipment will be acceptable.

Order, Payment and shipping terms:

Minimum Order
500kg per trial order. One PC of sample free of charge provided by approval and kept for future mass production inspection, delivery fees on buyer.

Production Capacity

500, 000MT/year

Sample Lead time

15-18working days include 7-10days making tooling if it's necessary.

Production lead time

10-20working days.

Description:

Item	Aluminum Extrusions of Electric Vehicle Charging Piles /EV Charging Pole
Material	Alloy 6063, 6061,6060,6005,6082 or according to customer' s choice
Temper	T4, T5, T6 ,T66
Surface	Anodize (clear, satin, bronze, black, golden, silver, other multicolor) , electrophoresis, powder coating, PVDF coating, wood grain painting, etc.
MOQ	1 ton. Usually 12 tons for a 20 feet container; 24 tons for a 40 feet container.
Profile type	Industry Aluminum profile used in cars, trains machinery ,trailers ,electronics, medical and other industrial filed .
Processing	Aluminium profile extruding ,Precise cutting,Straight rectification,Bending,Drilling,Tapping,Stamping,Pulling,CNC mill, CNC lathe. For precious machining and cutting, length tolerance can be 0.2mm, hole tolerance can be 0.05mm .
Moulding	1. Using our moulds, free; 2. Using customer' s drawing, opening mould fee need to be paid .
Certificate	ISO14001:2004, ISO9001:2000
Standard	Meet the China national standard GB/T6892-2006 and Europe standard EN12020-1,2(2001) and American standard AAMA611-98.
FOB Port	Shanghai, etc.

Applications:

Industry Aluminum profile used in cars, trains machinery ,electronics, medical and other industrial filed . In terms of hardware, machinery, electromechanical parts, solar PV products, aluminum frames are adopt as important auxiliary materials. We also have aluminum profiles for radiators, fitness machinery, buildings, lighting instrument, windpipes, oil pipelines, for instance.

Specifications:

1. Primary Technical Data

- 1)Chemical composition

Alloy	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Impurity	Al
6063	0.2-0.6	0.35	0.1	0.1	0.45-0.9	0.1	0.1	0.1	0.15	Rest
6061	0.4-0.8	0.7	0.15-0.4	0.15	0.8-1.2	0.04-0.35	0.25	0.15	0.15	Rest
6060	0.3-0.6	0.1-0.3	0.1	0.1	0.35-0.6	-	0.15	0.1	0.15	Rest
6005	0.6-0.9	0.35	0.1	0.1	0.40-0.6	0.1	0.1	0.1	0.15	Rest

2) Mechanical property

Alloy	Temper	Tensile strength	Yield strength	Elongation
6063	T5	≥ 160Mpa	≥ 110Mpa	≥ 8%
	T6	≥ 205Mpa	≥ 180Mpa	≥ 8%
6061	T6	≥ 265Mpa	≥ 245Mpa	≥ 8%

2.Specifications:

Excellent material for smooth and subtle edges.
Elegant appearance.
Surface treatment: colorful anodized or electrostatic powder coated.
Suitable for constructions and other industrial purposes.
Customized surface finishes are welcome.

Competitive Advantage:

- 1) Engineering design and support.
- 2) Aluminum profiles deeply processing:cutting,punching,drilling,milling,and fabricating.
- 3) High Quality system, strictly inspection during production and whole inspection before package.
- 4) Good performance, product warranty for 15 years.



+86-13861643436
 aluminum@hentec.com.cn
 aluminumextrusion-profiles.com

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421